



6T10BS-U3T

Micro ATX Tower



Features

- Compliant with Micro ATX specifications
- 0.6mm steel processed in a highly stable and modern design
- double-crimped, deburred edges
- One side screwed drives for easy assembly
- Removable HDD an decoupled bridge
- Glossy Front Panel
- two USB-ports and audio port in the front
- replaceable slot brackets
- enhanced slot-plates with EMI-protection
- lockable case
- TAC 2.0
- Optional: 1 x 8 or 9cm fan back

Toolless - Kit for 5,25“ and 3,5“ Drive assembly





6T10BS-U3T

Micro ATX Tower



Specifications

Housing Type	Mini Tower
Model	6T10
Dimensions with Front Bezel	385 x 175 x 350 mm (D/W/H)
Form Factor	Micro ATX
Housing Material	0.6 mm SECC - Steel
Weight	4,37 kg (5,53 kg Brutto)
Front Ports	2 x USB 3.0, HD Audio
Expansion Slots	4 Slots
Drive Space intern	1 x 3,5" (8,89cm)
Drive Space extern	2 x 5,25" (13,34cm) / 2 x 3,5" (8,89cm)
Maximum Length of Graphics	up to 21cm
Ordering Stock Hilden	6T10BS-U3T

